

# ISM7000 SERIES

## **Smart Mortise Entry Sets**


- BHMA/ANSI Grade 1, UL 3-hr fire rated commercial mortise lock that can be remotely locked, unlocked, and programmed using smartphone or BLE/WIFI gateway
- Intuitive mobile INOX app supports multiple users and properties with real time access management
- Entry function with easily programmable Privacy and Passage modes
- The Patent Pending lock is installed without special door prep and is battery powered

#### **FEATURES**

- · Motor-driven deadbolt provides auto-locking function
- Entry function with programmable Passage and Privacy modes with optional mechanical key override
- Passage mode can be activated with interior button
- Unit powered by 4 x AA alkaline batteries with secondary 9V power source for emergency access
- ANSI Grade 1 commercial mortise construction

#### **ACCESS**

- Smartphone App via Bluetooth
- Smartphone App remote access using BLE/WIFI gateway
- High Frequency 13.56MHz Card, FOB or Wristband
- Mechanical key and thumbturn
- INOX SMART App available on Apple and Google Play



#### **APPLICATION**

INOX ISM7000 BLE mortise lock is a perfect gateway solution across various applications

An entry lock for apartment unit, gym, laundry or office doors for multi-family/mixed-use properties, multitenant offices, retail/commercial facilities, or high-end residential entry doors

#### SECURITY COMPLIANCE

- Backend IoT PaaS complies with domestic and international information security standards, privacy and compliance requirements
- Backend IoT PaaS security covers data and cloud services











#### **FINISH**

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- PVD4 Satin Brass (243, 276 and 321 levers)
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze
- Please see Finish Solutions on INOX website for special order finishes








## APP CAPABILITIES

- Multi-level user Access and Permission Management
- Remote Locking and Unlocking via BLE/WIFI gateway
- Device Management and Personalization
- Do Not Disturb and DND Override functions
- Bluetooth mobile Locking and Unlocking
- Global Search function

- **Account Management and Settings**
- Property and Door Information Management
- Cloud-based encrypted authentication
- 2-step verification for added security
- Additional Bluetooth and Secure RFID credentials
- App and Web-based solutions

























Download the INOX SMART App












## LOCK SPECIFICATIONS

#### Lockcase Backset 2-3/4" (70mm)

Center to Center Distance	Lever to Cylinder: 3-7/8" (98mm)
	Lever to Thumbturn: 2-11/16" (68mm)
Handing	Specify handing when ordering
Cylinder	Schlage C keyway 6 pin, 1-1/4" mortise cylinder with 2 keys (standard). Optional SFIC and LFIC housing and cores available
CAM	CAM01-SCL Clover Cam
Material	Trim: Stainless Steel Lockcase: Heavy gauge Steel Bolt: Brass and Stainless Steel Faceplate/Strike: Stainless Steel Cylinder: Solid Brass






### CODE COMPLIANCE

- ANSI/BHMA A156.13 Grade 1 Mortise Lock
- UL Listed for 3 hour fire doors
- CAN/ULC S104 up to 3 hours
- UBC Standard 7-2 (1997) NFPA 252
- NFPA 80 National Fire Protection Fire Door Assembly
- NFPA101 National Fire Protection Life Safety
- ANSI A117.1 ADA Accessibility

### **COMPONENTS**



## Description

- Exterior heavy-duty stainless steel cast plate with choice of X Series lever designs
- 2 **Glareless Viewing Portal**
- 3 ISM7000 lockcase and faceplate; 2-3/4" backset
- 4 Interior sub-plate
- 5 Interior heavy duty stainless steel cast plate with choice of X Series lever designs
- 6 1/4" (6.35mm) adjustable strike
- 7 1" (25.4mm) heavy-duty deadbolt
- 8 Schlage C keyway, 6 pin 1-1/4" mortise cylinder **CMB1146**






#### **HOW TO ORDER ISM7000 SMART MORTISE ENTRY SET**

#### HOW TO ORDER LOCKSETS

Use the sequence below to order or specify mortise locksets. Please see price book for parts or additional service upcharges.



## **6** CYLINDER AND HOUSING (INCLUDES COLLAR)

LC = Less Cylinder



Blank = Standard Mortise 1-1/4" Cylinder



- -S6 = Small Format Interchangeable Cylinder (SFIC) Housing 1-1/4", 6-Pin, Less Core, L Clover Cam
- -S7 = Small Format Interchangeable Cylinder (SFIC) Housing 1-3/8", 7-Pin, Less Core, L Clover Cam
- -L6 = Large Format Interchangeable Cylinder (LFIC) Housing 1-1/2", 6-Pin, Less Core, L Clover Cam



Order IC Cores and Thick Door Kits (TDKs) separately - See Price Book

## **6** THUMBTURN





TT02

Blank = TT04

## **7** FINISH

Standard:







PVD4 finish available in the 243, 276 and 321 lever design

## 8 HANDING

RH = Right Hand

LH = Left Hand

RHR = Right Hand Reverse

LHR = Left Hand Reverse

