

ISM95 Smart Lock

For Sliding Doors

- Smart mortise locks that can be remotely locked, unlocked, and programmed from anywhere in the world
- Offers property owners and managers a platform to create an all-inclusive access management hub with unlimited properties, openings, and users
- Patented anti-binding winged deadbolt provides smooth operation for safety and security

LOCK/UNLOCK

- Smartphone APP, Connected Via Bluetooth
- Remote access using Wi-Fi or POE gateway
- High Frequency RF13.56 MHz card, fob, wristband
- Mechanical Key from outside or inside thumbturn
- Unit powered by 4 x AA alkaline batteries

LOCK SPECIFICATIONS

Door Thickness 1-3/4" (45mm) Standard

Backset 2-3/4" (70mm)
2-1/2" (63.5mm)

Center to Center Distance Lever to cylinder:
3-7/8" (98mm)
Lever to thumbturn:
2-11/16" (68mm)

Cylinder Schlage C keyway 6 pin, 1-1/4" mortise cylinder with 2 keys (standard). SFIC and LFIC housing and cores available

CAM CAM01-SCL Clover Cam

Material Trim: Stainless Steel
Lockcase: Heavy Gauge Steel
Deadbolt: Stainless Steel
Faceplate/Strike: Stainless Steel
Cylinder: Solid Brass

APPLICATION

Perfect keyless solution across a variety of applications, including commercial, mixed use, multi-tenant offices, and commercial/retail facilities. Commercial mortise lock that can be remotely locked, unlocked, and programmed using smartphone via Bluetooth or Wi-Fi gateway. Intuitive mobile app supports multiple users and properties with real-time access management.

CODE COMPLIANCE

- ANSI/BHMA 156.36 Auxiliary Locks
ABSU A117.1 Accessibility Code (ADA Compliant)
- Backend IoT PaaS complies with domestic and international information security standards, privacy and compliance requirements
- Backend IoT PaaS security covers data and cloud services



FINISH

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- PVD4 Satin Brass (243, 276 levers & PHIX330.512.8)
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze
- Please see Finish Solutions on INOX website for special order finishes

Outside Trim

RFID e-Keys
Reader and
Touch-To-Lock

Mechanical Key
with Standard
Mortise or
Interchangeable
Core Cylinder



Twelve Standard Stainless Steel
X-Series Levers and Designer
Surface Pull Options


Inside Trim

Communicates with
Smartphone via
Low Energy Bluetooth

Toggle Button for
Passage and
Privacy Mode

Thumbturn to
Mechanically Lock
& Unlock Deadbolt


Full Conceal Plate
Escutcheon Covers
4 x AA Batteries,
Electronics and Motor




Inside Lever Supports
Single Action
Emergency Egress

APP CAPABILITIES


- Multi-level user Access and Permission Management
- Remote Locking and Unlocking via BLE/WIFI gateway
- Device Management and Personalization
- Passage and Privacy Mode: One-Time and Scheduled
- Bluetooth & RFID Locking and Unlocking
- Global Search function
- Account Management and Settings
- Property and Door Information Management
- Cloud-Based Encrypted Authentication
- 2-step Verification Available for Added Security
- Audit Trail Shows All Lock/Unlock Activity
- App and Web-based solutions




Property List



Doors List




Lock / Unlock



Audit Trail




Add Devices



Passage/Privacy

COMPONENTS



Description

- 1 PD95 lockcase and faceplate; 2-3/4" backset PD95-234 or 2-1/2" backset PD95-212
- 2 1" (25.4mm) heavy-duty brass bolt throw with self-retracting non-marring hooks
- 3 Mounting sub-plate
- 4 Interior stainless steel plate with choice of X Series lever designs
- 5 Adjustable strike for deadbolt; up to 1/4" vertical adjustability (6.35mm)
- 6 Round Reader
- 7 Schlage C keyway, 6 pin 1-1/4" mortise cylinder
- 8 Exterior Surface Pull
- 9 Exterior heavy-duty stainless steel cast rose with choice of X Series lever designs

ISM95 Trim options:

Option 1: Interior SFR plate with choice of lever sectional with X series rose and lever on the outside

Option 2: Interior SFR plate with choice of lever sectional with Surface Pull on the outside





Option 1	Option 2	Exterior
✓	✓	Reader
✓	✓	Cylinder
✓	✓	X Series Rose with Lever
	✓	Surface Pull

HOW TO ORDER SMART SLIDING DOOR MORTISE LOCK

HOW TO ORDER LOCKSETS

Use the sequence below to order or specify mortise locksets. Please see price book for parts or additional service upcharges.

Outside Trim			Inside Trim			Lock	Backset	Reader	Bluetooth	Cylinder	Thumbturn	Finish	Handing
Smart	Rose	Lever	Plate	Lever	Lock	Backset	Reader	Bluetooth	Cylinder	Thumbturn	Finish	Handing	
ISM	-XGT	202	-SFR	202	-PD9550	A	-R1	-BRW	-S6		-32D	-LH	
	1	2	3	2	4	5	6		7	8	9	10	

ROSE	LEVER	PLATE	LOCK	BACKSET
 XGT XGS	 201 202 205 221 243 244 276 318 319 320 345 346	 SFR	Entry  6 READER R1	Backset Blank = 2-3/4" Backset A = 2-1/2"

7 CYLINDER AND HOUSING (INCLUDES COLLAR)

LC = Less Cylinder



Blank = Standard Mortise 1-1/4" Cylinder



-S6 = Small Format Interchangeable Cylinder (SFIC) Housing 1-1/4", 6-Pin, Less Core, L Clover Cam

-S7 = Small Format Interchangeable Cylinder (SFIC) Housing 1-3/8", 7-Pin, Less Core, L Clover Cam

-L6 = Large Format Interchangeable Cylinder (LFIC) Housing 1-1/2", 6-Pin, Less Core, L Clover Cam



Order IC Cores and Thick Door Kits (TDKs) separately - See Price Book

8 THUMBTURN



TT02



Blank = TT04

9 FINISH

Standard:



32D




C19G



C19



CGY



CDB



32



PVD4

PVD4 is available for 243 and 276 lever designs. For custom finish requests, please contact Sales.

10 HANDING

RH = Right Hand

LH = Left Hand














HOW TO ORDER SMART SLIDING DOOR MORTISE LOCK

HOW TO ORDER LOCKSETS

Use the sequence below to order or specify mortise locksets.

Surface Pull will need to be ordered as a separate line item. Please see price book for list of available pulls.

Smart	Surface Pull	Plate	Lever	Lock	Backset	Reader	Bluetooth	Cylinder	Thumbturn	Finish	Handing
ISM	-PH	-SFR	202	-PD9550	A	-R1	-BRW	-S6		-32D	-LH
	1	2	3	4	5	6		7	8	9	10

TRIM	LEVER	PLATE	LOCK	BACKSET
PH* - PHIX Pull	 201	 202	 205	 221
	 244	 276	 318	 319
	 345	 346	 320	
		 SFR	Entry	Backset Blank = 2-3/4" Backset A = 2-1/2"
				6 READER  R1

*Order surface pull separately - See Price Book for available pulls and finishes

7 CYLINDER AND HOUSING (INCLUDES COLLAR)

LC = Less Cylinder



Blank = Standard Mortise 1-1/4" Cylinder



-S6 = Small Format Interchangeable Cylinder (SFIC) Housing 1-1/4", 6-Pin, Less Core, L Clover Cam

-S7 = Small Format Interchangeable Cylinder (SFIC) Housing 1-3/8", 7-Pin, Less Core, L Clover Cam

-L6 = Large Format Interchangeable Cylinder (LFIC) Housing 1-1/2", 6-Pin, Less Core, L Clover Cam



Order IC Cores and Thick Door Kits (TDKs) separately - See Price Book

8 THUMBTURN



TT02



Blank = TT04

9 FINISH

Standard:



32D




C19G



C19



CGY



CDB



32



PVD4

PVD4 is available for PHIX330.512.8 ADA Pull. For custom finish requests, please contact Sales.

10 HANDING

RH = Right Hand

LH = Left Hand